

Single Inverter

General Description


The ETQ74LVC1G04 is an inverter operating from a 1.65V to 5.5V supply. This device is fabricated with advanced CMOS technology to achieve ultra-high speed with high output drive.

Features

- $\pm 24\text{mA}$ Sink and Source Output Capability
- Over-Voltage Tolerant Inputs and Outputs
- Designed for 1.65V to 5.5V VCC Operation
- These Devices are Pb-Free and are RoHS Compliant
- Multiple Package Options Automotive AEC-Q100 Grade 1 Qualified
 - Ambient Temperature Range of -40°C to $+125^{\circ}\text{C}$
 - ESD HBM $\pm 4\text{KV}$ PASS
 - ESD CDM $\pm 1\text{KV}$ PASS
 - Latch Up Current to $\pm 100\text{mA}$ PASS
- Part No. and Package Information

Part No.	Package	Packing Option	MSL
ETQ74LVC1G04	SC70-5(1.3mm $\times$ 2.1mm)	Tape and Reel, 3K/Reel	1
ETQ74LVC1G04T	SOT23-5(1.6mm $\times$ 2.9mm)	Tape and Reel, 3K/Reel	3
ETQ74LVC1G04Y	DFN6(1.0mm $\times$ 1.5mm)	Tape and Reel, 3K/Reel	1
ETQ74LVC1G04N	DFN6(1.0mm $\times$ 1.0mm)	Tape and Reel, 10K/Reel	1

Pin Configuration



ETQ74LVC1G04

Pin Function


SC70-5/ SOT23-5

Pin No.	Pin Name	Function
1	NC	No connect
2	A	Input
3	GND	Ground
4	Y	Output
5	VCC	Supply Voltage

DFN6

Pin No.	Pin Name	Function
1	NC	No connect
2	A	Input
3	GND	Ground
4	Y	Output
5	NC	No Connect
6	VCC	Supply Voltage

Block Diagram



Function Table

Input A	Output Y
L	H
H	L

ETQ74LVC1G04

Absolute Maximum Ratings

Symbol	Parameter		Value	Unit
V _{CC}	DC Supply Voltage(VCC Pin)		-0.5 to 6.5	V
V _I	DC Input Voltage ⁽¹⁾		-0.5 ≤ V _I ≤ 6.5	V
V _O	DC Output Voltage Output in Higher or Low State		-0.5 to V _{CC} + 0.5	V
I _{IK}	DC Input Diode Current V _I < GND		-50	mA
I _{OK}	DC Output Diode Current V _O < GND, V _O > V _{CC}		±50	mA
I _O	DC Output Sink Current		±50	mA
I _{CC}	DC Supply Current per Supply Pin		+100	mA
I _{GND}	DC Ground Current per Supply Pin		-100	mA
T _{STG}	Storage Temperature Range		-65 to 150	°C
T _L	Lead Temperature, Soldering 10 Seconds		260	°C
T _J	Max Junction Temperature		150	°C
V _{ESD}	ESD Classification	Human Body Model ⁽²⁾	±4000	V
		Charged Device Model ⁽³⁾	±1000	
I _{LU}	Max Latch Up Current Above V _{CC} and GND at 125°C ⁽⁴⁾		±100	mA

Stresses exceeding those listed in this table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Note1: IO absolute maximum rating must be observed.

Note2: HBM tested per AEC-Q100-002(JEDEC JS-001);

Note3: CDM tested per AEC-Q100-011(JEDEC JS-002);

Note4: Latch up Current Maximum Rating tested per AEC-Q100-004(JEDEC JESD78F).

Thermal Characteristics

Symbol	Package	Ratings	Value	Unit
R _{θJA}	SC70-5	Thermal Characteristics, Thermal Resistance, Junction-to-Air	300	°C/W
	SOT23-5		250	
	DFN6(1.0mm × 1.5mm)		440	
	DFN6(1.0mm × 1.0mm)		440	

Recommended Operating Conditions

Symbol	Parameter		Min	Max	Unit
V _{CC}	DC Supply Voltage		1.65	5.5	V
	Operating Date Retention		1.5	5.5	
V _{IN}	DC Input Voltage		0	5.5	V
V _{OUT}	DC Output Voltage (High or Low State)		0	5.5	V
T _A	Operating Temperature Range		-40	125	°C
t _r , t _f	Input Rise and Fall Time	V _{CC} = 2.5 V ± 0.2 V	0	20	ns/V
		V _{CC} = 3.0 V ± 0.3 V	0	10	
		V _{CC} = 5.0 V ± 0.5 V	0	5	

ETQ74LVC1G04

Electrical Characteristics

DC Electrical Characteristics

Symbol	Parameter	Condition	V _{CC} (V)	T _A = 25 °C			-40°C ≤ T _A ≤ 125°C		Unit
				Min	Typ	Max	Min	Max	
V _{IH}	High-Level Input Voltage		1.65 to 1.95 2.3 to 5.5	0.75V _{CC} 0.7V _{CC}			0.75V _{CC} 0.7V _{CC}		V
V _{IL}	Low-Level Input Voltage		1.65 to 1.95 2.3 to 5.5			0.25V _{CC} 0.3V _{CC}		0.25V _{CC} 0.3V _{CC}	V
V _{OH}	High-Level Output Voltage	I _{OH} = -100μA	1.65 to 5.5	V _{CC} -0.1	V _{CC}		V _{CC} -0.1		V
		I _{OH} = -3mA	1.65	1.29	1.4		1.29		
		I _{OH} = -8mA	2.3	1.9	2.1		1.9		
		I _{OH} = -12mA	2.7	2.2	2.4		2.2		
		I _{OH} = -16mA	3.0	2.4	2.7		2.4		
		I _{OH} = -24mA	3.0	2.3	2.5		2.3		
		I _{OH} = -32mA	4.5	3.8	4.0		3.8		
V _{OL}	Low-Level Output Voltage	I _{OH} = 100μA	1.65 to 5.5		0.0	0.1		0.1	V
		I _{OL} = 3mA	1.65		0.08	0.24		0.24	
		I _{OL} = 8mA	2.3		0.20	0.3		0.3	
		I _{OL} = 12mA	2.7		0.22	0.4		0.4	
		I _{OL} = 16mA	3.0		0.28	0.4		0.4	
		I _{OL} = 24mA	3.0		0.38	0.55		0.55	
		I _{OL} = 32mA	4.5		0.42	0.55		0.55	
I _{IN}	Input Leakage Current	V _{IN} = 5.5V or GND	0 to 5.5		±0.1			±1.0	μA
I _{OFF}	Power Off Leakage Current	V _{IN} = 5.5V or V _{OUT} = 5.5V	0			1		10	μA
I _{CC}	Quiescent Supply Current	V _{IN} = 5.5V or GND	5.5					10	μA

ETQ74LVC1G04

AC Electrical Characteristics

$t_r = t_f = 5\text{ns}$; $C_L = 50\text{pF}$; $R_L = 500\Omega$.

Symbol	Parameter	Condition	$V_{CC}(\text{V})$	$T_A = 25^\circ\text{C}$			$-40^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$		Unit
				Min	Typ	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay (Figure3 and4)	$R_L = 1\text{M}\Omega$, $C_L = 15\text{pF}$	1.65	2.0	5.3	11.4	2.0	12.0	ns
			1.8	2.0	4.4	9.5	2.0	10.0	
		$R_L = 1\text{M}\Omega$, $C_L = 15\text{pF}$	2.5 ± 0.2	0.8	3.0	6.5	0.8	7.0	
		$R_L = 1\text{M}\Omega$, $C_L = 15\text{pF}$	3.3 ± 0.3	0.5	2.4	4.5	0.5	4.7	
				1.5	2.5	5.5	1.5	5.2	
		$R_L = 500\Omega$, $C_L = 50\text{pF}$	5.0 ± 0.5	0.5	2.0	3.9	0.5	4.1	
		$R_L = 1\text{M}\Omega$, $C_L = 15\text{pF}$		0.8	2.4	4.3	0.8	4.5	

Capacitive Characteristics

Symbol	Parameter	Condition	Typ	Unit
C_{IN}	Input Capacitance	$V_{CC} = 5.5\text{V}$, $V_I = 0\text{V}$ or V_{CC}	2.5	pF
C_{PD}	Power Dissipation Capacitance ⁽⁵⁾	10MHz, $V_{CC} = 3.3\text{V}$, $V_I = 0\text{V}$ or V_{CC}	26	pF
		10MHz, $V_{CC} = 5.5\text{V}$, $V_I = 0\text{V}$ or V_{CC}	30	

Note5: C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:

f_i = input frequency in MHz;

f_o = output frequency in MHz;

C_L = output load capacitance in pF;

V_{CC} = supply voltage in V;

N = number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

AC Test Circuit




Figure 3. Switching Waveform





Figure4. Test Circuit

ETQ74LVC1G04

Package Dimension

SC70-5(1.3mm × 2.1mm)




COMMON DIMENSIONS

(Unit: mm)

SYMBOL	MIN	NOM	MAX
A	-	-	1.05
A1	0	-	0.15
b	0.17	-	0.33
c	0.12	-	0.20
D	2.00	2.10	2.20
e	0.65BSC		
e1	1.30BSC		
E	2.20	2.30	2.40
E1	1.21	1.30	1.35
L	0.50REF		
L1	0.33REF		

ETQ74LVC1G04

SOT23-5(1.6mm × 2.9mm)




COMMON DIMENSIONS

(Unit: mm)

SYMBOL	MIN	NOM	MAX
A	-	-	1.25
A1	0	-	0.15
b	0.36	-	0.50
c	0.12	-	0.20
D	2.75	2.9	3.05
e	0.90	0.95	1.00
e1	1.80	1.90	2.00
E	2.60	2.80	3.00
E1	1.45	1.6	1.75
L	0.60REF		
L1	0.30	0.45	0.60

ETQ74LVC1G04

DFN6 (1.0mm × 1.5mm)




COMMON DIMENSIONS

(Unit: mm)

SYMBOL	MIN	NOM	MAX
A	0.34	0.37	0.40
A1	0	0.02	0.05
A3	0.10REF		
b	0.10	0.15	0.20
D	0.95	1.00	1.05
E	0.95	1.00	1.05
e	0.30	0.35	0.40
H	0.10REF		
K	0.15	--	--
L	0.35	0.40	0.45
L1	0.075REF		

ETQ74LVC1G04

DFN6 (1.0mm × 1.0mm)



COMMON DIMENSIONS

(Unit: mm)

SYMBOL	MIN	NOM	MAX
A	0.34	0.37	0.40
A1	0	0.02	0.05
A3	0.10REF		
b	0.10	0.15	0.20
D	0.95	1.00	1.05
E	0.95	1.00	1.05
e	0.30	0.35	0.40
H	0.10REF		
K	0.15	--	--
L	0.35	0.40	0.45
L1	0.075REF		

ETQ74LVC1G04

Revision History and Checking Table

Version	Date	Revision Item	Modifier	Function & Spec Checking	Package & Tape Checking
1.0	2017-07-19	Original Version	Ma Yong jian	Ma Yong jian	Ma Yong jian
1.1	2021-06-25	Update DC/AC Table	Ma Yong jian	Ma Yong jian	Ma Yong jian
1.2	2022-05-18	Add DFN6(1X1)	Shi bo	Shi bo	Shi bo
1.3	2022-06-10	ESD Update	Shi bo	Shi bo	Shi bo
1.4	2022-08-03	Update DFN6(1X1)	Shi bo	Shi bo	Shi bo
1.5	2022-10-14	Update format and Thermal Characteristics	Wu han	Shi bo	Shi bo
1.6	2023-11-30	Update Pin table/ESD	Shi bo	Shi bo	Shi bo
1.7	2025-06-07	Add Packing Option	Yang xiaoxu	Yang xiaoxu	Liu jiaying
1.8	2025-10-15	Update Format	Wang anran	Yang xiaoxu	Liu jiaying