

Single 2-Input OR Gate

General Description


The ET74AHC1G32 is a single 2-input OR Gate in three tiny footprint packages. The device performs much as LCX multi-gate products in speed and drive.

Features

- Designed for 2V to 5.5V V_{CC} Operation
- ±8mA Balanced Output Sink and Source Capability
- Over-voltage Tolerant Inputs Accept Voltages to 5.5V
- These Devices are Pb-Free and RoHS Compliant
- ESD Protection Complies with JESD22 Standard
 - HBM: ±4000V Pass (JEDEC JS-001)
 - CDM: ±1000V Pass (JEDEC JS-002)
- Latch-up Performance Exceeds ±100mA per JEDEC JESD78F
- Part No. and Package Information

| Part No. | Package | Packing Option | MSL |
|--------------|-------------------------|------------------------|-----|
| ET74AHC1G32 | SC70-5 (1.3mm × 2.1mm) | Tape and Reel, 3K/Reel | 1 |
| ET74AHC1G32T | SOT23-5 (1.6mm × 2.9mm) | Tape and Reel, 3K/Reel | 3 |
| ET74AHC1G32Y | DFN6 (1.0mm × 1.5mm) | Tape and Reel, 3K/Reel | 1 |

Pin Configuration



ET74AHC1G32

Pin Function


SC70-5/ SOT23-5

| Pin No. | Pin Name | Function |
|---------|----------|----------------|
| 1 | A | Input A |
| 2 | B | Input B |
| 3 | GND | Ground |
| 4 | Y | Output Y |
| 5 | VCC | Supply Voltage |

DFN6

| Pin No. | Pin Name | Function |
|---------|----------|----------------|
| 1 | A | Input A |
| 2 | B | Input B |
| 3 | GND | Ground |
| 4 | Y | Output Y |
| 5 | NC | No Connect |
| 6 | VCC | Supply Voltage |

Block Diagram



Function Table

| Input | | Output |
|-------|---|--------|
| A | B | Y |
| L | L | L |
| L | H | H |
| H | L | H |
| H | H | H |

ET74AHC1G32

Absolute Maximum Ratings

| Symbol | Parameter | | Value | Unit |
|------------------|---|-------------------------------------|-------------------------------|------|
| V _{CC} | DC Supply Voltage (VCC Pin) | | -0.5 to 7.0 | V |
| V _I | DC Input Voltage ⁽¹⁾ | | -0.5 ≤ V _I ≤ 7.0 | V |
| V _O | DC Output Voltage Output in Higher or Low State | | -0.5 to V _{CC} + 0.5 | V |
| I _{IK} | DC Input Diode Current, V _I < GND | | -50 | mA |
| I _{OK} | DC Output Diode Current, V _O < GND, V _O > V _{CC} | | ±50 | mA |
| I _O | DC Output Sink Current | | ±50 | mA |
| I _{CC} | DC Supply Current Per Supply Pin | | 100 | mA |
| I _{GND} | DC Ground Current Per Supply Pin | | -100 | mA |
| T _{STG} | Storage Temperature Range | | -65 to 150 | °C |
| T _L | Lead Temperature, Soldering 10 Seconds | | 260 | °C |
| T _J | Max Junction Temperature | | 150 | °C |
| V _{ESD} | ESD Classification | Human Body Model ⁽²⁾ | ±4000 | V |
| | | Charged Device Model ⁽³⁾ | ±1000 | |
| I _{LU} | Latch Up Current Above V _{CC} and GND at 125°C ⁽⁴⁾ | | ±100 | mA |

Stresses exceeding those listed in this table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Note1: I_O absolute maximum rating must be observed.

Note2: HBM tested per JEDEC JS-001;

Note3: CDM tested per JEDEC JS-002;

Note4: Latch Up Current Maximum Rating tested per JEDEC JESD78F.

Thermal Characteristics

| Symbol | Package | Ratings | Value | Unit |
|------------------|---------|--|-------|------|
| R _{θJA} | SC70-5 | Thermal Characteristics, Thermal Resistance, Junction-to-Air | 300 | °C/W |
| | SOT23-5 | | 250 | |
| | DFN6 | | 440 | |
| P _D | SC70-5 | Power Dissipation in Still Air at 85°C | 215 | °C/W |
| | SOT23-5 | | 260 | |
| | DFN6 | | 150 | |

ET74AHC1G32

Recommended Operating Conditions

| Symbol | Parameter | Min | Max | Unit |
|-----------------|---------------------------------------|-----|-----------------|------|
| V _{CC} | DC Supply Voltage Operating | 2 | 5.5 | V |
| V _I | DC Input Voltage | 0 | V _{CC} | V |
| V _O | DC Output Voltage (High or Low State) | 0 | V _{CC} | V |
| T _A | Operating Temperature Range | -40 | 125 | °C |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied.

Electrical Characteristics

DC Electrical Characteristics

| Symbol | Parameter | Condition | V _{CC} (V) | T _A = 25°C | | | -40°C ≤ T _A ≤ 125°C | | Unit |
|------------------|---------------------------|--|---------------------|-----------------------|-----------------|------|--------------------------------|------|------|
| | | | | Min | Typ | Max | Min | Max | |
| V _{IH} | High-Level Input Voltage | | 2.0 | 1.5 | | | 1.5 | | V |
| | | | 3.0 | 2.1 | | | 2.1 | | |
| | | | 5.5 | 3.85 | | | 3.85 | | |
| V _{IL} | Low-Level Input Voltage | | 2.0 | | | 0.5 | | 0.5 | V |
| | | | 3.0 | | | 0.9 | | 0.9 | |
| | | | 5.5 | | | 1.65 | | 1.65 | |
| V _{OH} | High-Level Output Voltage | I _{OH} = -50uA | 2~5.5 | V _{CC} - 0.1 | V _{CC} | | V _{CC} - 0.1 | | V |
| | | I _{OH} = -4mA | 3 | 2.58 | | | 2.4 | | |
| | | I _{OH} = -8mA | 4.5 | 3.54 | | | 3.7 | | |
| V _{OL} | Low-Level Output Voltage | I _{OL} = 50uA | 2~5.5 | | | 0.1 | | 0.1 | V |
| | | I _{OL} = 4mA | 3 | | | 0.36 | | 0.55 | |
| | | I _{OL} = 8mA | 4.5 | | | 0.36 | | 0.55 | |
| I _{IN} | Input Leakage Current | V _I = 5.5V or GND | 0~5.5 | | | 0.1 | | 2.0 | uA |
| I _{OFF} | Power Off Leakage Current | V _I = 5.5V or V _O = 5.5V | 0 | | | 1 | | 10 | μA |
| I _{CC} | Quiescent Supply Current | V _I = 5.5V or GND | 5.5 | | | 1 | | 40 | uA |

AC Electrical Characteristics

t_r = t_f = 3ns

| Symbol | Parameter | Condition | V _{CC} (V) | T _A = 25°C | | | -40°C ≤ T _A ≤ 125°C | | Unit |
|--------------------------------------|--------------------------------------|-----------------------|---------------------|-----------------------|-----|------|--------------------------------|------|------|
| | | | | Min | Typ | Max | Min | Max | |
| t _{PLH} t _{PHL} | Propagation Delay (Figure3 and 4) | C _L = 15pF | 3~3.6 | | 7.5 | 11 | 1 | 13.5 | ns |
| | | C _L = 50pF | 3~3.6 | | 9.5 | 16 | 1 | 19 | |
| | | C _L = 15pF | 4.5~5.5 | | 6.4 | 8.4 | 1 | 9.9 | |
| | | C _L = 50pF | 4.5~5.5 | | 7.9 | 10.4 | 1 | 12.4 | |

ET74AHC1G32

Capacitance Characteristics

| Symbol | Parameter | Condition | Typ | Unit |
|----------|--|---|-----|------|
| C_{IN} | Input Capacitance | $V_{CC} = 5.5V, V_I = 0V \text{ or } V_{CC}$ | 2.5 | pF |
| C_{PD} | Power Dissipation Capacitance ⁽⁵⁾ | 10MHz, $V_{CC} = 3.3V, V_I = 0V \text{ or } V_{CC}$ | 21 | pF |
| | | 10MHz, $V_{CC} = 5.5V, V_I = 0V \text{ or } V_{CC}$ | 21 | |

Note5: C_{PD} is used to determine the dynamic power dissipation (P_D in μW).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \sum(C_L \times V_{CC}^2 \times f_o) \text{ where:}$$

f_i = input frequency in MHz;

f_o = output frequency in MHz;

C_L = output load capacitance in pF;

V_{CC} = supply voltage in V;

N = number of inputs switching;

$\sum(C_L \times V_{CC}^2 \times f_o)$ = sum of outputs.

AC Test Circuit




Figure3. Switching Waveform





Figure4. Test Circuit

ET74AHC1G32

Package Dimension

SC70-5 (1.3mm × 2.1mm)




COMMON DIMENSIONS

(Unit: mm)

| SYMBOL | MIN | NOM | MAX |
|--------|---------|------|------|
| A | - | - | 1.10 |
| A1 | 0.00 | - | 0.15 |
| b | 0.15 | - | 0.35 |
| c | 0.08 | - | 0.20 |
| D | 2.00 | 2.10 | 2.30 |
| e | 0.65BSC | | |
| e1 | 1.30BSC | | |
| E | 2.15 | 2.30 | 2.50 |
| E1 | 1.15 | 1.30 | 1.45 |
| L | 0.50REF | | |
| L1 | 0.33REF | | |

ET74AHC1G32

SOT23-5 (1.6mm × 2.9mm)




COMMON DIMENSIONS

(Unit: mm)

| SYMBOL | MIN | NOM | MAX |
|--------|---------|------|------|
| A | - | - | 1.45 |
| A1 | 0.00 | - | 0.15 |
| b | 0.28 | 0.35 | 0.50 |
| c | 0.08 | 0.15 | 0.22 |
| D | 2.75 | 2.9 | 3.05 |
| e | 0.90 | 0.95 | 1.00 |
| e1 | 1.80 | 1.90 | 2.00 |
| E | 2.60 | 2.80 | 3.00 |
| E1 | 1.45 | 1.6 | 1.75 |
| L | 0.60REF | | |
| L1 | 0.30 | 0.45 | 0.60 |

ET74AHC1G32

DFN6 (1.0mm × 1.5mm)



COMMON DIMENSIONS


(Unit: mm)

| SYMBOL | MIN | NOM | MAX |
|--------|---------|------|------|
| A | 0.50 | -- | 0.60 |
| A1 | 0.00 | 0.02 | 0.05 |
| A3 | 0.10REF | | |
| b | 0.15 | 0.20 | 0.25 |
| D | 0.90 | 1.00 | 1.10 |
| E | 1.40 | 1.50 | 1.60 |
| e | 0.50BSC | | |
| K | 0.30REF | | |
| K1 | 0.25REF | | |
| L | 0.35 | 0.40 | 0.45 |
| L1 | 0.30 | 0.35 | 0.40 |


ET74AHC1G32

Tape Information


SC70-5 (1.3mm × 2.1mm)



SOT23-5 (1.6mm × 2.9mm)





DFN6 (1.0mm × 1.5mm)



ET74AHC1G32

Marking Information

| | |
|---|--|
|  |  |
| ET74AHC1G32 A132 = Part Number X = Tracking Number | ET74AHC1G32T A132 = Part Number XXXXX = Tracking Number |

Revision History and Checking Table

| Version | Date | Revision Item | Modifier | Function & Spec Checking | Package & Tape Checking |
|---------|------------|------------------|------------|--------------------------|-------------------------|
| 1.0 | 2025-09-05 | Original Version | Wang anran | Yang xiaoxu | Liu jiaoying |